



技术参数 Specifications

使用线数 (Hole count): 2 4 6 8 12 14 16 20
 温度范围 (Temperature range): -25°C ~ 85°C
 额定电压 (Rated voltage): 250V. AC/DC
 额定电流 (Rated current): 5A

端子 Terminal

图号 Pic	型号 Type	描述 Description	厚度 Thickness	材质 Material	表面处理 Surface treatment	压线范围 WireRange		尺寸 Dimension(mm)			对照表 Comparison No.	最小包装量 Minimum packing
						AWG#	mm ²	W	L	E		
B	小 5556	横连式 Horizontal chain	0.2	磷铜 Phosphor copper	镀亮锡 Bright tin plating	24~22	0.2~0.3	1.2	11.5	3.6	公头 Male	12000

塑料件 Plastic parts

线数 Hole count	针座 Receptacle for male terminal	公头 Plug for female terminal
2		ZT3200 (小 5557-2P)
4		ZT3201 (小 5557-4P)
6		ZT3202 (小 5557-6P)

塑料件 Plastic parts

线数 Hole count	针座 Receptacle for male terminal	公头 Plug for female terminal
8		<p>ZT3203 (小 5557-8P)</p> <p>1 2 3 4 5 6 7 8</p>
12		<p>ZT3204 (小 5557-12P)</p> <p>1 2 3 4 5 6 7 8 9 10 11 12</p>
14		<p>ZT3205 (小 5557-14P)</p> <p>1 2 3 4 5 6 7 8 9 10 11 12 13 14</p>
16		<p>ZT3206 (小 5557-16P)</p> <p>1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16</p>

塑料件 Plastic parts

线数 Hole count	针座 Receptacle for male terminal	公头 Plug for female terminal																				
20		<p>ZT3209 (小 5557-20P)</p>  <table border="1" data-bbox="874 680 1214 745"> <tr> <td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td> </tr> <tr> <td>11</td><td>12</td><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18</td><td>19</td><td>20</td> </tr> </table>	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
1	2	3	4	5	6	7	8	9	10													
11	12	13	14	15	16	17	18	19	20													